

L4.800



规格 Specifications:

4边额定输出功率:(THD=1% 1KHz):
.....8欧姆CH1/800W+CH2/800W+CH3/800W+CH4/800W
.....4欧姆CH1/1200W+CH2/1200W+CH3/1200W+CH4/1200W
桥接输出功率(THD=1% 1KHz):
.....8欧姆 CH1/CH2 2480W+CH3/CH4 2480W
.....4欧姆 CH1/CH2 3240W+CH3/CH4 3240W
最大平方根电压(THD=1% 1KHz):CH1/80V+CH2/80V+CH3/80V+CH4/80V
回转比率(at 1KHz):34V/us
输入灵敏度 (在额定输出, 1KHz):0.775V/1.0V/1.4V
总谐波失真 (在10%额定功率下,1KHz): <0.1%
互调失真标准(60Hz 7KHz): <0.1%
互调失真 (3.15KHz 15KHz): <0.1%
串音(1KHz在10%额定功率下):<-80dB
频响(ref 1kHz): 20Hz...20kHz (0-2dB)
输入电阻(20Hz...20KHz ,balanced): 20k Ω /平衡,10K Ω 非平衡
阻尼系数 (at100Hz /1KHz 8 Ω):>300
信噪比 (A weighted): 105dB
电源要求:AC-230V 50Hz-60Hz)
保护:限幅, 热保护, 短路
散热:前面板到后面板
尺寸(WxDxH):483x430x88mm
净重:31kg
毛重:33kg